


STANDARD DETAIL NOTES:
THIS IS A DIAGRAMMATIC REPRESENTATION AND CERTAIN DETAILS REMOVED FOR CLARITY.
IMPORTANT: ALL DIMENSIONS INDICATED ARE NOMINAL.
ESTIMATED O/A ASSEMBLY DRY WEIGHT: 30.0kW - 473.00kg's, 37.0kW - 488.00kg's

IMPORTANT:
THIS DATA IS RELEASED FOR
REFERENCE ONLY.

REVISION		THIS DATA REMAINS THE PROPERTY OF STALKER ENGINEERING. NO DATA MAY BE REPRODUCED WITHOUT PRIOR CONSENT OF COMPANY. DATA MAY BE ALTERED WITHOUT NOTIFICATION.	GENERAL TOLERANCES METRIC +/-0.400mm IMPERIAL +/-0.015"		DRWN: AR	 STALKER PUMPS www.stalkerpumps.com.au
		AS1100 3rd ANGLE PROJECTION	REFERENCE: ORIG FILE REF. 14/09/2005	DATE: UPDATED 06/02/2007	DIMENSION OUTLINE DIAGRAMMATIC ISO 65/40 -315 DC FLEX JAW SPACER COUPLING 30kW and 37kW 200L 2P BASE FRAME MOUNTED	
			DO NOT SCALE	APPRVD:		