

STANDARD DETAIL NOTES:


THIS IS A DIAGRAMMATIC REPRESENTATION AND CERTAIN DETAILS REMOVED FOR CLARITY.

IMPORTANT: ALL DIMENSIONS INDICATED ARE NOMINAL.

ESTIMATED O/A ASSEMBLY DRY WEIGHT: 2.2kW - 136.00kg's, 3.0kW - 146.00kg's

IMPORTANT:

THIS DATA IS RELEASED FOR
REFERENCE ONLY.

REVISION		THIS DATA REMAINS THE PROPERTY OF STALKER ENGINEERING. NO DATA MAY BE REPRODUCED WITHOUT PRIOR CONSENT OF COMPANY. DATA MAY BE ALTERED WITHOUT NOTIFICATION.		GENERAL TOLERANCES METRIC +/-0.400mm IMPERIAL +/-0.015"		DRWN: AR	 STALKER PUMPS www.stalkerpumps.com.au	
		AS1100 3rd ANGLE PROJECTION		REFERENCE: ORIG FILE REF. 14/07/2006		DATE: UPDATED 06/02/2007		
		DO NOT SCALE		APPRVD:	CHECKED:	SCALE: DIAGRAMMATIC		DIMENSION OUTLINE DIAGRAMMATIC ISO 80/50-200 DC SPACER COUPLING 2.20kW AND 3.0kW 4P 100L BASE FRAME MOUNTED
						FILE REF: REFER DWG NUMBER		DRAWING No: 3900ISODCSPCLEM03435BFDIMA3
							A3	