


ESTIMATED O/A ASSEMBLY DRY WEIGHT: 2.2kw - 164.00kg's, 3.0kW - 174.00kg's

THIS DATA IS RELEASED FOR  
REFERENCE ONLY.

REVISION		THIS DATA REMAINS THE PROPERTY OF STALKER ENGINEERING. NO DATA MAY BE REPRODUCED WITHOUT PRIOR CONSENT OF COMPANY. DATA MAY BE ALTERED WITHOUT NOTIFICATION.	<b>GENERAL TOLERANCES</b> METRIC    +/-0.400mm IMPERIAL   +/-0.015"		DRWN: AR	 <b>STALKER PUMPS</b> <a href="http://www.stalkerpumps.com.au">www.stalkerpumps.com.au</a>
		AS1100 3rd ANGLE PROJECTION	REFERENCE: ORIG FILE REF. 20/01/2005, UPDATED 01/12/2005	DATE: UPDATED 06/02/2007	DIMENSION OUTLINE DIAGRAMMATIC ISO 80/50-250 DC FLEX JAW SPACER COUPLING 2.2 & 3.0kW 4P 100L BASE FRAME MOUNTED	
		<b>DO NOT SCALE</b>	APPRVD:	CHECKED:	FILE REF: REFER DWG NUMBER	DRAWING No: <b>4000ISODCSPCPLEM03435BFDIMA3</b>