\top \top \top **STANDARD DETAIL NOTES:** 315.00 MAX THIS IS A DIAGRAMMATIC REPRESENTATION AND CERTAIN DETAILS REMOVED FOR CLARITY. IMPORTANT: ALL DIMENSIONS INDICATED ARE NOMINAL. 25.00 56.00 205.00 DISCHARGE 25.00 1" (25mm) BSPT FEMALE THRD. 1.25" (32mm) BSPT FEMALE THRD Π Ш SUCTION 200.00Ø 50.00 90.00g 312.00 MAX 310.00 MIN 40.00 **KEYWAY** 24.00Ø j6 8×7 KEY 50.00 48.00 110.00 10.00 11.50Ø x 4 2 - M6 HX HDS. @ 76.00 ctr's HORIZONTAL POSITION 50.00 40.00 140.00 ctr's 18.00 ctr's IMPORTANT: 170.00 76.00 THIS DATA IS RELEASED FOR REFERENCE ONLY. DRWN: AR THIS DATA REMAINS THE PROPERTY OF STALKER **GENERAL TOLERANCES** ENGINEERING, NO DATA MAY BE REPRODUCED METRIC +/-0.400mm WITHOUT PRIOR CONSENT OF COMPANY. DATA MAY BE www.stalkerpumps.com.au DATE: IMPERIAL +/-0.015" REVISION ALTERED WITHOUT NOTIFICATION 12/08/2004 DIMENSION OUTLINE DIAGRAMMATIC REFERENCE: GA 1600DCGAA2.dwg SCALE: **AS1100 3rd ANGLE PROJECTION** 25APR DC SERIES DIAGRAMMATIC APPRVD: CHECKED: FILE REF: **DRAWING No: DO NOT SCALE A3 1600DCDIMA3** REFER DWG NUMBER
